


N and P-Channel Enhancement Mode Power MOSFET

Features

- Excellent $R_{DS(on)}$ and Low Gate Charge
- N-Channel
 $V_{DS}=30V, I_D=3.6A$
 $R_{DS(on)} < 58m\Omega @ V_{GS}=10V$
- P-Channel
 $V_{DS}=-30V, I_D=-2A$
 $R_{DS(on)} < 130m\Omega @ V_{GS}=-10V$




Mechanical Characteristics

- Package: SOT-23-6
- Packaging: Tape and Reel per EIA 481
- Marking : Making Code


Applications

- DC/DC Converter
- Load Switch for Portable Devices

Marking : Making Code



Schematic Diagram



Absolute Maximum Rating (Ratings at 25 °C ambient temperature unless otherwise specified.)

Parameter	Symbols	Value		Unit
Drain-Source Voltage	V_{DS}	30	— 30	V
Gate-Source Voltage	V_{GS}	± 20		V
Drain Current-Continuous	I_D	3.6	— 2	A
Drain Current-Pulsed ^{Note1}	I_{DM}	15	— 10	A
Junction Temperature	P_D	1.2		W
Maximum Power Dissipation	T_J	150		°C
Storage Temperature Range	T_{STG}	-55 to +150		°C

Thermal Characteristics

Thermal Resistance, Junction-to-Ambient Note2	$R_{\theta JA}$	104	°C/W
---	-----------------	-----	------

Electrical Characteristics(Tc=25°C Unless otherwise specified)**N-Channel**

Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	30	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=30V, V_{GS}=0V$	--	--	1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	--	--	± 100	nA
Gate Threshold Voltage ^{Note3}	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	1.2	1.5	2.2	V
Drain-Source On-Resistance ^{Note3}	$R_{DS(on)}$	$V_{GS}=10V, I_D=3.6A$	--	40	50	m Ω
		$V_{GS}=4.5V, I_D=3A$	--	58	73	m Ω
Forward Transconductance ^{Note3}	g_{FS}	$V_{DS}=5V, I_D=3.6A$	--	11	--	S
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{DS}=15V, V_{GS}=0V, f=1MHz$	--	230	--	pF
Output Capacitance	C_{oss}		--	40	--	pF
Reverse Transfer Capacitance	C_{rss}		--	17	--	pF
Switching Characteristics						
Turn-on Delay Time	$t_{d(on)}$	$V_{DS}=15V, I_D=3.6A,$ $V_{GS}=4.5V, R_G=6\Omega$	--	10	--	nS
Turn-on Rise Time	t_r		--	50	--	nS
Turn-off Delay Time	$t_{d(off)}$		--	10	--	nS
Turn-off Fall Time	t_f		--	20	--	nS
Total Gate Charge	Q_g	$V_{DS}=15V, I_D=3.6A, V_{GS}=10V$	--	4	--	nC
Gate-Source Charge	Q_{gs}		--	0.75	--	nC
Gate-Drain Charge	Q_{gd}		--	0.65	--	nC
Source-Drain Diode Characteristics						
Diode Forward Voltage ^{Note3}	V_{SD}	$V_{GS}=0V, I_S=3.6A$	--	--	1.2	V
Diode Forward Current ^{Note2}	I_S		--	--	3.6	A







Electrical Characteristics($T_c=25^{\circ}\text{C}$ Unless otherwise specified)**P-Channel**






Parameter	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$-V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	30	--	--	V
Zero Gate Voltage Drain Current	$-I_{DSS}$	$V_{DS}=-30V, V_{GS}=0V$	--	--	1	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	--	--	± 100	nA
Gate Threshold Voltage ^{Note3}	$-V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	1	1.6	2.5	V
Drain-Source On-Resistance ^{Note3}	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-2A$	--	75	130	m Ω
		$V_{GS}=-4.5V, I_D=-1.5A$	--	115	180	m Ω
Forward Transconductance ^{Note3}	g_{FS}	$V_{DS}=-10V, I_D=-2A$	--	2	--	S
Dynamic Characteristics						
Input Capacitance	C_{iss}	$V_{DS}=-15V, V_{GS}=0V, f=1MHz$	--	226	--	pF
Output Capacitance	C_{oss}		--	47	--	pF
Reverse Transfer Capacitance	C_{rss}		--	28	--	pF
Switching Characteristics						
Turn-on Delay Time	$t_{d(on)}$	$V_{DS}=-15V, R_L=15\Omega$ $V_{GS}=-10V, R_G=6\Omega$	--	9	--	nS
Turn-on Rise Time	t_r		--	9	--	nS
Turn-off Delay Time	$t_{d(off)}$		--	18	--	nS
Turn-off Fall Time	t_f		--	6	--	nS
Total Gate Charge	Q_g	$V_{DS}=-15V, I_D=-2A, V_{GS}=-10V$	--	8.5	--	nC
Gate-Source Charge	Q_{gs}		--	2.3	--	nC
Gate-Drain Charge	Q_{gd}		--	1.5	--	nC
Source-Drain Diode Characteristics						
Diode Forward Voltage ^{Note3}	$-V_{SD}$	$V_{GS}=0V, I_S=-2A$	--	--	1.2	V
Diode Forward Current ^{Note2}	$-I_S$		--	--	2	A

Note: 1. Repetitive Rating: Pulse width limited by maximum junction temperature.







2.Surface Mounted on FR4 Board, $t \leq 10$ sec.3.Pulse Test: Pulse width $\leq 300\mu s$, duty cycles $\leq 2\%$






N-Channel Typical Characteristics Curves






P-Channel Typical Characteristics Curves






Outline Drawing – SOT-23-6(Dimensions in mm)**Package Information**

Package Type	Description	Quantity (pcs)	Standard
SOT-23-6	Reel -7 inches	3000	EIA-481

Conditions of Soldering and Storage

- Recommended condition of reflow soldering



adjust the following parameters:

- | |
|--|
| • Time length of peak temperature (longer) |
| • Time length of soldering (longer) |
| • Thickness of solder paste (thicker) |

• **Conditions of hand soldering**


- | |
|----------------------|
| • Temperature: 300°C |
| • Time: 3s max |
| • Times: one time |

• **Storage conditions**


- | |
|--|
| • Temperature: 5 to 40° C |
| • Humidity: 30 to 80% RH |
| • Recommended period: One year after manufacturing |

Package Specifications

• **The method of packaging**




Embossed tape and reel data



Symbol	Value(unit:mm)
A	$\varnothing 177.8 \pm 1$
B	2.7 ± 0.2
C	$\varnothing 13.5 \pm 0.2$
E	$\varnothing 54.5 \pm 0.2$
F	12.3 ± 0.3
D	$9.6 + 2 / - 0.3$
T1	1.0 ± 0.2
T2	1.2 ± 0.2

Reel (7")



Tape (8mm)

Contact Information

TANI website: <http://www.tanisemi.com> Email: tani@tanisemi.com

For additional information, please contact your local Sales Representative.

 is registered trademarks of TANI Corporation.

Product Specification Statement

The product specification aims to provide users with a reference regarding various product parameters, performance, and usage. It presents certain aspects of the product's performance in graphical form and is intended solely for users to select product and make product comparisons, enabling users to better understand and evaluate the characteristics and advantages of the product. It does not constitute any commitment, warranty, or guarantee.

The product parameters described in the product specification are numerical values, characteristics, and functions obtained through actual testing or theoretical calculations of the product in an independent or ideal state. Due to the complexity of product applications and variations in test conditions and equipment, there may be slight fluctuations in parameter test values. TANI shall not guarantee that the actual performance of the product when installed in the customer's system or equipment will be entirely consistent with the product specification, especially concerning dynamic parameters. It is recommended that users consult with professionals for product selection and system design. Users should also thoroughly validate and assess whether the actual parameters and performance when installed in their respective systems or equipment meet their requirements or expectations. Additionally, users should exercise caution in verifying product compatibility issues, and TANI assumes no responsibility for the application of the product. TANI strives to provide accurate and up-to-date information to the best of our ability. However, due to technical, human, or other reasons, TANI cannot guarantee that the information provided in the product specification is entirely accurate and error-free. TANI shall not be held responsible for any losses or damages resulting from the use or reliance on any information in these product specifications.

TANI reserves the right to revise or update the product specification and the products at any time without prior notice, and the user's continued use of the product specification is considered an acceptance of these revisions and updates. Prior to purchasing and using the product, users should verify the above information with TANI to ensure that the product specification is the most current, effective, and complete. If users are particularly concerned about product parameters, please consult TANI in detail or request relevant product test reports. Any data not explicitly mentioned in the product specification shall be subject to separate agreement.

The design of the product is intended to meet civilian needs and is not guaranteed for use in harsh environments or precision equipment. It is not recommended for use in systems or equipment such as medical devices, aircraft, nuclear power, and similar systems, where failures in these systems or equipment could reasonably be expected to result in personal injury. TANI shall assume no responsibility for any consequences resulting from such usage.

Users should also comply with relevant laws, regulations, policies, and standards when using the product specification. Users are responsible for the risks and liabilities arising from the use of the product specification and must ensure that it is not used for illegal purposes. Additionally, users should respect the intellectual property rights related to the product specification and refrain from infringing upon any third-party legal rights. TANI shall assume no responsibility for any disputes or controversies arising from the above-mentioned issues in any form.